

# UNIFLEX® Prezentare Generala / Prese atelier

## S 1

Forta presare (kN / Tone) 750 / 75  
Diametru maxim presare (Ø) 52 mm



## S 2

Forta presare (kN / Tone) 900 / 90  
Diametru maxim presare (Ø) 63 mm



## HM 200 Ecoline / HM 200 / HM 250 / HM 260

Forta presare (kN / Tone) 1300 / 130 (HM 260: 650/65)  
Diametru maxim presare (Ø) 70 mm



## S 6 / S 6 Ecoline

Forta presare (kN / Tone) 1600 / 160  
Diametru maxim presare (Ø) 78 mm



## S 7

Forta presare (kN / Tone) 2400 / 240  
Diametru maxim presare (Ø) 82 mm

## HM 290 / HM 290 Ecoline

Forta presare (kN / Tone) 2400 / 240  
Diametru maxim presare (Ø) 111 mm



## S 8i

Forta presare (kN / Tone) 2200 / 220  
Diametru maxim presare (Ø) 139 mm



## S 10i

Forta presare (kN / Tone) 2800 / 280  
Diametru maxim presare (Ø) 139 mm

Producatorul isi rezerva dreptul de a modifica datele tehnice  
fara notificare prealabila

# UNIFLEX® Prezentare Generala / Prese de mare productivitate

## HM 220 B

Forta presare (kN / Tone) maximum 1400 / 140  
 Diametru maxim presare (Ø) 70 mm



<b>HM 325i B</b>	
Forta presare (kN / Tone)	2800 / 280
Diametru maxim presare (Ø)	161 mm
<b>HM 375i B</b>	
Forta presare (kN / Tone)	3150 / 315
Diametru maxim presare (Ø)	161 mm
<b>HM 380i B</b>	
Forta presare (kN / Tone)	3400 / 340
Diametru maxim presare (Ø)	161 mm

## HM 420i B

Forta presare (kN / Tone) 3150 / 315  
 Diametru maxim presare (Ø) 161 mm  
 Deschidere fara bacuri 280 mm (11")



<b>HM 660i B</b>	
Forta presare (kN / Tone)	6000 / 600
Diametru maxim presare (Ø)	325 mm
<b>HM 665i B</b>	
Forta presare (kN / Tone)	4500 / 450
Diametru maxim presare (Ø)	380 mm

Producatorul isi rezerva dreptul de a aduce modificari tehnice fara notificare prealabila.

## UNIFLEX® Masini speciale



### **KS 6, KS 8i Masina calibrare**

Forta presare (kN / Tone) 600 / 60, 800 / 80  
Diametru maxim presare 55 mm, 114 mm  
Tip bacuri presare PBK 239 / PBK 237

### **HM 245 Presa tip C**

Forta presare (kN / Tone) 600 / 60  
Diametru maxim presare 70 mm  
Tip bacuri presare PB 239



### **HM 500**

Forta presare (kN / Tone) 3800 / 380  
Diametru maxim presare 180 mm  
Tip bacuri presare PB 239L / PB 232L / PB 554



### **HM 502**

Forta presare (kN / Tone) 5000 / 500  
Diametru maxim presare 180 mm  
Tip bacuri presare PB 239L / PB 232L / PB 554

### **HM 660i B PFC**

Forta presare (kN / Tone) 6000 / 600  
Diametru maxim presare 325 mm  
Tip bacuri presare PB 239L / PB 237L / PB 246



### **HM 420i B PFC**

Forta presare (kN / Tone) 3150 / 315  
Diametru maxim presare 161 mm  
Tip bacuri presare PB 239L / PB 237L

### **HM 3xxi B PFC**

Forta presare (kN / Tone) 2900 / 290  
Diametru maxim presare 161 mm  
Tip bacuri presare PB 239L / PB 237L

Producatorul isi rezerva dreptul de a aduce modificari tehnice fara notificare prealabila.